

Photon Life PK31

Photon Life PK31 Home Projector









- Photon Life Perfect for any room in the house
- 4K UHD RGB LED Technlology 900 lumens that brings bold and clear visuals. Perfect for movie nights or gaming with friends, the Photon Life 100 delivers stunning performance with up to 30,000 hours of virtually maintenance-free viewing.
- Quick and easy setup Lightweight design with Auto vertical keystone for simple and flexible setup
- Built in speaker No need for extra equipment with the 5W built-in speaker



Bring 4K to any room with the Optoma Photon Life PK31. Enjoy ultra-sharp visuals with 900 ISO lumens, HDR, and 90% DCI-P3 colour. With LED tech, 30,000 hours of virtually maintenance-free viewing, built-in audio & easy setup—cinema just got portable.

Specifications

Net weight

EAN: 5055387668966, Colour: Black The following specifications are preliminary and subject to change without notice Display/image Display technology DLP® Resolution UHD (3840x2160) Brightness 900 lumens Brightness (HK) 1,600 Contrast ratio 400.1 Contrast ratio - dynamic 200.000:1 Native aspect ratio 16:9 Aspect ratio - compatible 4:3,16:9 Keystone correction - vertical 30° Has vertical auto keystone Yes correction 23-240Khz Horizontal scan rate Vertical scan rate 15-255Hz Uniformity 90% 1.52m ~ 3.81m (60" ~ 150") diagonal Screen size Lamp info 3 LED Light source type LED life 30,000 hours Optical Throw ratio 1.5:1 ~ 1.65:1 Projection distance 1.99m - 5.47m / 78.35" - 215.35" Zoom 1.1 Zoom type Manual Focal length 15.8 ~ 17.4 Native offset 105% Connectivity Connections Inputs 1 x HDMI 2.0 Outputs 1 x USB-A power 2A, 1 x Audio 3.5mm General Noise level (min) 30dB Noise level (max) 32dB PC compatibility VGA_60, VGA_72, VGA_75, VGA_85, VGA_120, SVGA_56, SVGA_60, SVGA_72, SVGA_75, SVGA_85, SVGA_120, XGA_60, XGA_70, XGA_75, XGA_120, SXGA_75, SXGA_85, SXGA_60, SXGA_72, SXGA_75, SXGA_85, QuadVGA_75, SXGA+_60, UXGA_60, Mac G4, MAC13, Mac G4, Mac G4, MAC19, MAC21, WXGA_60, WXGA_75, WXGA_85, WXGA_60, WXGA_60, WXGA_120-RB, WXGA+_60, 1680x1050_60, 1920x1080_RB, 1920x1080_EIA 1920x1080_120, 1920x1080_240, 1920x1200-RB, 2560x1440_60 (RB), 2560x1440_120 (RB), 3840x2160_30, 480i, 480p, 576i, 576p, 720p_60, 720p_50, 1080i_60, 1080i_50, 1080p, 2160/24P, 2160/25P, 2160/30P, 2160/50P, 2D compatibility 2160/60P 3D compatibility Full 3D 3D Security Kensington Lock IP5X (Optical Engine only) IP rating 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, OSD / display languages Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 24/7 operation Yes 360° operation Yes Operating conditions Operating Altitude: Without high altitude mode, 0°C~35°C@1499m above sea level. With high altitude mode, 0°C~30°C@1500m~3000m above sea level. Non-Operating Altitude: 30°C@0~12,200m above sea level. Remote control Speaker count Watts per speaker 5W In the box Adaptor (150W) Remote control Basic user manual 2x AAA Battery Input lag 4.60ms Power VAC 100-240V (50/60Hz) Power supply 0.5W Power consumption (standby) Power consumption (min) 53W Power consumption (max) 110W Weight and dimensions 238 x 215 x 130 mm / 9.37" x 8.46" x 5.12" Dimensions (W x D x H) Gross weight 4 kg / 8.82 lbs

2.2 kg / 4.85 lbs

Copyright © 2025, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 06082025094531