

GT2160HDR

First 4K UHD Short-throw Cinema Gaming Projector









- First 4K UHD Short-throw Cinema Gaming Projector
- Bright Room Design with Brightness 4,000 lumens & 1,200,000:1 Contrast
- HDR 10 & HLG Supported for Brightest Whites, Deepest Darks, and Lifelike Colors
- Ultimate Gaming Experience supporting lightingfast 240Hz refresh rate, and low 4ms Input Lag in Enhanced Gaming Mode



Featuring the lightning-fast refresh rate and the low input lag, GT2160HDR is perfectly quenching your desire for the ultimate home entertainment, no matter in movie watching or gaming. With true 4K UHD resolution, GT2160HDR will bring the immersive cinema and gaming experiences up to 300" screen. The different display options also allows optimized performance in cinema mode, gaming mode, or 3D mode, delivering images and motions with ultimate smoothness and clarity.

Specifications

Gross weight

Net weight

Display/image DIPTM Display technology Resolution UHD (3840x2160) Brightness 4,000 lumens Contrast ratio 1,200,000:1 16:9 Native aspect ratio 4:3.16:9.16:10 Aspect ratio - compatible Keystone correction -+/-20° horizontal Keystone correction - vertical +/-20° Horizontal scan rate 31 ~ 135Khz Vertical scan rate 24 ~ 120Hz 80% Uniformity 0.93m \sim 7.63m (36.43" \sim 300.53") diagonal Screen size Lamp info Light source type Lamp life hours (up to) 4000 (Bright), 15000 (Dynamic), 10000 (Eco) Optical 0.49:1 Throw ratio Projection distance 0.4m - 3.3m Zoom Zoom type Fixed 7.51mm Focal length Lens shift Vertical +0% Native offset 116% Connectivity Connections Inputs 2 x HDMI 2.0 Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power Control 1 x RS232, 1 x 12V trigger General Noise level (typical) 27dB 28dB Noise level (max) UHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, PC compatibility VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 2D compatibility Frame Packing(1280x720@50Hz/60Hz, 1920x1080@23.98/24Hz), Frame Sequential(800x600@120Hz, 3D compatibility 1024x768@120Hz, 1280x800@120Hz, 1920x1080@120Hz), Side by Side(1920x1080@50(25)Hz, 1920x1080@60(30)Hz) 3D 3D ready Security Security bar, Kensington Lock, Password protected interface OSD / display languages 11 languages: Dutch, English, French, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max Operating conditions humidity 85% Remote control Backlit home remote Speaker count Watts per speaker In the box AC power cord Remote control Basic user manual Input lag 4.00ms Power Power supply 100 ~ 240V, 50 ~ 60Hz 0.5W Power consumption (standby) Power consumption (min) 210W Power consumption (max) 330W Weight and dimensions Dimensions (W x D x H) 315 x 270 x 118

5 kg

3.8 kg

